

PRECISION SPINE
REFORM[®] Ti HA
HA COATED TITANIUM PEDICLE SCREW SYSTEM

STABLE FIXATION

Patent-pending Reform[®] Ti HA Coated Pedicle Screws have a hydroxyapatite coating applied to the screw threads that is designed to enhance the amount of fixation possible between the pedicle screw and the surrounding bone in osteoporotic patients. The Reform Ti HA Coated Pedicle Screw System features a low profile titanium tulip that reduces risk of facet impingement and the triple lead thread increases the speed and efficiency of screw delivery while reducing fatigue in creating all thoracolumbar constructs. Thirty degrees of angulation in all planes increases intraoperative flexibility. A minimally tapered screw thread lowers screw insertion torque while optimizing pull-out strength. A more aggressive self-starting screw tip optimizes initial bone engagement and the system's enlarged T25 drive feature provides stability during insertion. Hexalobular drive fittings on the bone screw and locking cap help reduce the incidence of toggle and stripping. The square threaded locking cap geometry is designed to reduce the risk of cross-threading. Sterile packaging prevents implant contamination.




TITANIUM TULIP



SELF-STARTING TIP



TRIPLE LEAD THREAD



PRECISION SPINE[®]

Discover the Difference




REFORM® Ti HA PEDICLE SCREW

Polyaxial Screws provide 30° angulation in all planes for intraoperative flexibility

Modified Proximal Tapered Thread design increases bone screw interface, enhancing pull-out strength while reducing insertion torque



Triple Lead Thread allows for efficient screw delivery




Self Starting Thread Tip allows for more immediate bone engagement, reliable insertion



Low Profile Titanium Tulip increases space for fusion while decreasing potential risk of adjacent segment facet impingement



T25 Drive Fittings on Bone Screw and Locking Cap reduces incidence of toggle and stripping



Square Threaded Locking Cap geometry reduces risk of cross threading



Full complement of offset connectors, dominoes, hooks and cross connectors increase procedure flexibility

Reform Ti HA Sizing

4.5mm Diameter	5.5mm Diameter	6.5mm Diameter	7.5mm Diameter	8.5mm Diameter
25mm	30mm	30mm	35mm	40mm
30mm	35mm	35mm	40mm	45mm
35mm	40mm	40mm	45mm	50mm
40mm	45mm	45mm	50mm	55mm
45mm	50mm	50mm	55mm	60mm
		55mm		70mm
				80mm

Reform Rod Sizing – ø5.5mm

Ti Straight	Ti Curved	CoCr Straight	CoCr Curved
80mm	35-80mm (5mm)	80mm	35-80mm (5mm)
100mm	90-120mm (10mm)	100mm	90-120mm (10mm)
120mm		120mm	
200mm		200mm	
300mm		300mm	
400mm		400mm	
500mm		500mm	

Precision Spine, Inc.
 2050 Executive Drive, Pearl, MS 39208
 Customer Service: 1.888.241.4773
 Phone: 601.420.4244
 Toll Free: 877.780.4370
 Fax: 601.420.5501
www.precisionspineinc.com



CE 2797